WORMS ENTREPRISES

GENERATOR RANGE

ACCESS 4000 i

SINGLE PHASE
230 V / 50 Hz
GASOLINE

MAX OUTPUT
4 kW

LONG RUN
TANK

SOUND PROOF
67 dB(A) at 7 m

WHEELS & HANDLE
INCLUDED





3 YEARS WARRANTY

Qualigen

INVERTER

AUTOMATIC IDLING SYSTEM

x2 PARALLEL CAPABILITY

Equipped with the inverter technology, this generator delivers a perfect quality of current, voltage and a very stable frequency which make it possible to use even with the most sensitive devices (computers, electronic equipments…). Equipped with the automatic idling system, the engine speed can be automatically adjusted to the required power which reduces consumption and noise. Transportable and soundproofed, this unit is ideal for all types of users and applications, professional, on site and leisure activities. With its coupling function, you can connect in parallel two ACCESS 4000 i and double the available power. It gives you a more powerful generator avoiding the question of additional weight and dimension increase.

		ACCESS 4000 i
Type		1 phase
Voltage regulator		**INVERTER**
Maximum AC output	kW	4
Continuous operating power (COP)	kW	3.6 (7.2 kW paired)
Maximum Amps	A	17.3
AC voltage	V	230
Frequency	Hz	50
Noise level EEC (LwA)	dB(A)	92
Noise level @ 7 m	dB(A)	67
Engine		WORMS G225-i
Maximum output	HP	5
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	10
Run Time (@ ¾ of the continuous output)	h	5
Dimensions L x W x H	mm	610 x 460 x 550
Packaging dimensions L x W x H	mm	625 x 490 x 565
Net weight	kg	42
Gross weight	kg	44.5
Reference		200000007
Reference standard version + DIFF		200000007.1

STANDARD EQUIPMENT

- ✔ 4-stroke OHV gasoline engine
- ✔ Recoil starter
- ✔ Oil sensor with warning light
- ✔ Automatic idling system
- ✔ 2 Single phase sockets 10/16 A Schuko 230 V
- 1 Single phase socket 10/16 A Schuko 230 V with Circuit breaker kit option
- ✔ Sockets protected by thermal circuit breaker
- ✔ USB charger
- ✔ Parallel operation socket
- ✔ Electronic overload protection with warning light
- ✔ Sound proof canopy
- ✔ Integrated wheels and carrying handle

OPTIONAL EQUIPMENT

- ✔ Cables for parallel operation (29W00001)
- ✔ Circuit breaker kit (factory option): 30 mA circuit breaker in Box + Copper Ground Rod

The constructor reserves the right to modify its machines without prior notice. Photographs, descriptions and characteristics are for indicative purpose and cannot commit the constructor.

Édition : 20261102

ZAC DE LAMIRAULT, 39 rue de Lamirault, 77090 COLLEGIEN FRANCE
Tel : (+33) 1 64 76 29 50