MASTER®
CLIMATE SOLUTIONS

DSH1128

FAN

CDX 20



FUNCTIONING PRINCIPLES



The air flow is forced by a radial fan. The air is sucked in by the upper inlet of the device and outlet takes place in the front part of the device. The fan has the ability to work in 2 speed modes.

TECHNICAL DATA

Power	kW	1 2	**0,161** **0,179**	Current	A	1 2	**0,7** **0,85**
Power source			Electrical	Voltage	V		**230**
Net weight	kg		**7,8**	Frequency	Hz		**50**
Gross weight	kg		**9**				

Speed mode		**1**	**2**	
Air flow	m³/h	**1270**	**1610**	
Pressure	Pa			
Noisy level	dBa	**67**	**70**	

PACKING

Dimensions packing	mm	**550x435x230**
Dimensions utilization	mm	**520x425x215**
Pieces for Euro-pallet	n°	**28**
Pieces per truck 80m^3	n°	**924**

COMPONENTS

Motor	**Asynchronous, monophase, with thermal protection, 2 speed mode: 1200/ 1400 rpm**

ACCESSORIES

WIRING DIAGRAM

M	:	**Motor**
C	:	**Capacitor**
P	:	**Power cord**
S	:	**Switch**
O	:	**Overcurrent protector**
T	:	**Time meter**

