TOTAL CLASSIC 15W-40



“TOTAL CLASSIC, the guaranteed quality”

Multigrade oil for all gasoline and Diesel, formulation using a set of additives with carefully selected performance and proportions to answer to the quality standards of the Association of the European Manufacturers (ACEA).

APPLICATIONS

Gasoline & Diesel	▪ Particularly recommended for all gasoline and Diesel engines in cars and light vans. ▪ Permits use at all temperature, any type of service, in town or on the motorway.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications	ACEA	A3/B3
	API	SL/CF

CUSTOMERS BENEFITS

Detergent capability	▪ Detergent-dispersant capability keeping engine components clean and, in particular, preventing the formation of black sludge and the build-up of particles.
Thermal stability	▪ Good thermal stability and oxidation resistance preventing any premature damage at high temperature.
Anti-wear	▪ Good anti-wear properties, particularly in the timing system. ▪ Shear stability ensuring satisfactory lubrication in service.
Lead-free	▪ Effective in engines using lead-free fuel and completely harmless to catalytic converters.

CHARACTERISTICS

TOTAL CLASSIC 15W-40	Units	Grade 15W-40
Density at 15°C	kg/m3	884
Viscosity at 40°C	mm2/s	113.4
Viscosity at 100°C	mm2/s	13.9
Viscosity Index	-	136
Pour Point	°C	-30
Flash Point	°C	230

The typical characteristics mentioned represent mean values.

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.