MOTIP Bitumen Undercoating 1 l

Technical Information



Beskytt understellet av bilen mot svake syrer og baser med MOTIP Bitumen Undercoating. Bitumenbasert underlakk er motstandsdyktig mot været og svake syrer og baser og har en utmerket rustforebygging. Bitumenbasert underbelegg forblir fleksibelt og er lydabsorberende.

Bestillingsnummer: 000033

Kvalitet og egenskaper

Skal påføres med en UBC spraypistol
Forblir fleksibel
Utmerket vedheft
Motstandsdyktig mot værpåvirkninger
Motstandsdyktig mot svake syrer og baser
Utmerket korrosjonsforebygging
Lydabsorberende

Fysiske og kjemiske data

Base: Bitumen
Kolourname: black
Lukt: Karakteristisk
Effektivitet: 1,00 L – 2 - 3 m²
Støvtørr: 60 min
Overflater: Underside of vehicles
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt: 9
Lagringsstabilitet: 5 y
Innhold: 1,00 L

Hvordan bruke

Les instruksjonene nøye før bruk.
Fjern løs gammel lakk og rust og slip overflaten med sandpapir.
Overflaten skal være ren, tørr og fri for fett. Boksen skal ha romtemperatur. Best resultat får du mellom 15 til 25 °C.
Rist boksen godt før bruk. Arbeidstrykk 4 til 5 bar.
Påfør underbelegget i ønsket lagtykkelse.
Rengjør spraypistolen med white spirit etter bruk
Tørketiden avhenger av omgivelsestemperaturen, luftfuktigheten og tykkelsen på den påførte lakken.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com