MOTIP Finishing Putty

Technical Information



Utjevn små, overfladiske ujevnheter i overflater av stål, aluminium, tre og polyester på bilen din med hurtigtørkende MOTIP Finishing Putty. Etterbehandlingskitt har en fin struktur og er lett å slipe. MOTIP Finishing kitt kan sprayes på nytt med alle lakksystemer og kan påføres i lag opp til 0,5 mm.

Bestillingsnummer: 000063

Kvalitet og egenskaper

Lett å slipe
Hurtigtørkende
Kan sprayes på nytt med alle lakksystemer
Svært fin struktur
Utmerket vedheft

Fysiske og kjemiske data

Kolourname: olive green
Lukt: Karakteristisk
Grad av glans: matt, 10 ±2
Kan slipes etter: 2-3 h
Flammepunkt: 24-29 °C
Lagringsstabilitet: 2 y
Innhold: 250 G

Hvordan bruke

Les instruksjonene nøye før bruk.
Best resultat får du mellom 15 til 25 °C.
Overflaten skal være ren, tørr og fri for fett. Fjern løs gammel lakk og rust og slip overflaten med sandpapir.
Påfør etterbehandlingskittet i ønsket lagtykkelse med en applikator.
Tørketiden avhenger av omgivelsestemperaturen.
Rengjør verktøyene som brukes, direkte etter bruk.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com