# MOTIP Polyester Fibre Putty (Profi)

## Technical Information




Universal two-component polyester putty to level irregularities in surfaces of steel, aluminium, wood, concrete and polyester. Polyester putty is elastic and very easy to sand. Polyester putty is re-sprayable with all lacquer systems and resistant to chemicals and the weather. Polyester putty can be applied in layers with a thickness up to 2 cm.

**Bestillingsnummer:** 000084

### Kvalitet og egenskaper

Ease of working
Easy to sand
Very good adherence
Resistant to weak acids and bases, propellants, solvents, water and de-icing salt
Free of asbestos and silicone
Short curing time

### Fysiske og kjemiske data

Base: Polyester resin with mineral fillers
Kolourname: grey
Lukt: Characteristic
Grad av glans: mat, 10 ±2
Helt tørr: 30 min
Overflater: Steel, aluminium, wood, concrete, polyester
Minimum arbeidstemperatur: 10
Maksimal arbeidstemperatur: 25
Flammepunkt: 31
Hardere prosentandel: 2.5 %
Lagringsstabilitet: 2 years
Innhold: 1,50 KG

### Hvordan bruke

Before use, carefully read the directions on the packaging and act accordingly.
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
Take the requested portion of putty compound out of the can and mix it well with the corresponding quantity of hardener.
Apply the mixed material in the desired layer thickness.
Clean tools immediately after use, if necessary with a nitro thinner. Do not return mixed material into the can.
After approx. 20-30 minutes the repaired spot can be drilled, sanded, sawed, rasped and painted.
The drying time depends on the ambient temperature.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of August 5, 2025** – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com