MOTIP Plastic Primer

Technical Information



MOTIP Plastic Primer for behandling av ubehandlede overflater av ulike typer plast. MOTIP Plastic Primer gir utmerket vedheft, krever ikke sliping og kan sprayes på nytt med all maling.

Bestillingsnummer: 04063, 880103

Kvalitet og egenskaper

Hurtigtørkende
Utmerket vedheft
Kan sprayes på nytt med alle lakksystemer
Ikke egnet for behandling av PE

Fysiske og kjemiske data

Base: Polyolefinharpiks
Kolourname: no colour
Lukt: Karakteristisk
Grad av glans: matt, 10 ±2
Effektivitet:
- 400 ML – 2.0 - 3.0 m²
- 150 ML – 0.75 -1.2 m²

Støvtørr: 10 min
Helt tørr: 10 - 15 min
Overstrøkbar: 10 - 15 min
Overflater:
- Several types of plastic.
- car parts, garden furniture and other objects of coatable hard plastics

Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt:
- n.a.
- n.a. °C

Temperaturbestandighet: 110 °C
Lagringsstabilitet: 10 y
Innhold:
- 400 ML
- 150 ML

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com

Hvordan bruke

Les instruksjonene nøye før bruk.
Forbehandling: Overflaten skal være ren, tørr og fri for fett. Når ønskelig, slip overflaten litt, grovhet 600.
Behandling: Overflaten skal være ren, tørr og fri for fett. Boksen skal ha romtemperatur. Beste behandlingstemperatur er mellom 10 og 25 °C.
Rist boksen i 2 minutter og spray en prøve før bruk. Avstand til overflaten som skal behandles skal være ca. 25 til 30 centimeter.
Påfør plastprimeren i maksimalt to (2) tynne lag. Etter tørking, uten sliping, kan sprayes på nytt med alle lakksystemer.
Rengjør spraydysen etter bruk (snu boksen opp ned og trykk på spraydysen i ca. 5 sekunder).
Tørketiden avhenger av omgivelsestemperaturen, luftfuktigheten og tykkelsen på den påførte lakken.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com