# MOTIP 1K Wash Primer

## Technical Information




MOTIP 1K Wash Primer er en universell en-komponent etsegrunning, egnet for flere ubelagte metalloverflater, som stål, galvanisert stål, rustfritt stål og aluminium. 1K Wash Primer kan belegges på nytt med MOTIP 1K eller 2K Primer/Filler. Etsevirkningen til 1K Wash Primer sikrer god vedheft av de neste lagene på den bare overflaten.

**Bestillingsnummer:** 04122

### Kvalitet og egenskaper

Hurtigtørkende
Utmerket vedheft
Sveisbar
Utmerket korrosjonsbeskyttelse
Egnet for punktreparasjon

### Fysiske og kjemiske data

Base: Nitrocellulose harpiks
Kolourname: red
Lukt: Karakteristisk
Grad av glans: matt, 10 ±2
Effektivitet: 500 ML – 1.5 m²
Støvtørr: 10 - 20 min
Tørr å ta på: 20 - 30 min
Helt tørr: 30 min
Overstrøkbar: 30 min
Overflater: Steel, galvanized steel, stainless steel and aluminium
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt: n.a.
Temperaturbestandighet: 90 °C
Lagringsstabilitet: 10 y
Innhold: 500 ML

### Hvordan bruke

Les instruksjonene nøye før bruk.
Overflaten skal være ren, tørr og fri for fett. Fjern løs gammel lakk og rust og slip overflaten med sandpapir.
Rist boksen i 2 minutter og spray en prøve før bruk. Beste behandlingstemperatur er mellom 10 og 25 °C.
Påfør 1-2 tynne lag av vaskegrunningen, med en avstand på ca. 15 til 20 centimeter til overflaten som skal behandles.
Rengjør spraydysen etter bruk (snu boksen opp ned og trykk på spraydysen i ca. 5 sekunder).
Tørketiden avhenger av omgivelsestemperaturen, luftfuktigheten og tykkelsen på den påførte lakken.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of August 5, 2025** – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com