MOTIP Leather & Vinyl Paint

Technical Information



Reparer og pynt vinyl-, skinn- og kunstskinndeler på bilen din, for eksempel bilseter med MOTIP Leather & Vinyl Paint. Skinn og vinylmaling har en varig farge og opprettholder den opprinnelige strukturen.

Bestillingsnummer: 04238, 04237, 04236, 04235, 04234, 04233, 04232, 04231, 04230

Kvalitet og egenskaper

Varig farge og varig glans
Elastisk
Utmerket vedheft
Opprettholder den opprinnelige strukturen

Fysiske og kjemiske data

Base: Nitrocellulose harpiks
Kolourname:
- brown
- white
- beige
- beige brown
- grey
- beige grey
- black

Lukt: Karakteristisk
Grad av glans: matt, 10 ±2
Effektivitet: 200 ML – 0.75 m²
Støvtørr: 5 - 10 min
Tørr å ta på: 10 - 20 min
Helt tørr: 120 min
Overstrøkbar: 120 min
Overflater: Vinyl, leather and artificial leather
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt: n.a.
Temperaturbestandighet: 110 °C
Lagringsstabilitet: 10 y
Innhold: 200 ML

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com

Hvordan bruke

Les instruksjonene nøye før bruk.
Overflaten skal være ren, tørr og fri for fett.
Ubehandlede deler skal dekkes til.
Boksen skal ha romtemperatur. Beste behandlingstemperatur 10 til 25 °C. Rist boksen i 2 minutter og spray en prøve før bruk.
Avstand til overflaten som skal behandles skal være ca. 25 til 30 centimeter.
Påfør vinylsprayen i flere tynne lag. Før du påfører neste lag, må du riste boksen igjen.
Rengjør spraydysen etter bruk (snu boksen opp ned og trykk på spraydysen i ca. 5 sekunder).
Tørketiden avhenger av omgivelsestemperaturen, luftfuktigheten og tykkelsen på den påførte lakken.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of November 3, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com