MOTIP Fugemasse

Technical Information



Tetningsskjøter, kant-til-kant-skjøter, spor og overlapping i bil-, vogn- og containerkonstruksjon med MOTIP Sealant. Spesielt nyttig for tetting av sveisepunkter foran og bak på biler og på steder som er vanskelige å nå i bagasjerommet og interiøret i kjøretøyet. Egenskaper: Siden den er svært stabil og behandlet nesten fiberfri, har MOTIP børstebar fugemasse en nesten original overflatestruktur. Tetningsmassen har utmerkede klebeegenskaper på ubehandlede, grunnede, malte og galvaniserte metallplater. Tetningsmassen tørker raskt, slik at den raskt kan males over med all maling som normalt er tilgjengelig. Fugemassen tåler temperaturer fra -25 °C til +80 °C.

Bestillingsnummer: 07505

Kvalitet og egenskaper

Fysiske og kjemiske data

Base: Syntetisk harpiks
Kolourname: grey
Overflater: For sealing of joints, edge-to-edge joints, grooves and overlapping in car, carriage and container construction.
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Innhold: 750 ml

Hvordan bruke

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com