MOTIP Assembly Grease

Technical Information



Forhindre slitasje og klebing av skruforbindelser som er utsatt for store arbeidsbelastninger MOTIP Assembly Grease. Monteringsfett er vannavstøtende og har en utmerket korrosjonsforebygging.

Bestillingsnummer: 090310

Kvalitet og egenskaper

Ekstremt egnet for montering av bremsesystemer
Forenkler fremtidig fjerning
Høy termisk stabilitet
Forhindrer slitasje og feste
Motstandsdyktig mot vann, salt og svake syrer og baser
Rettet jetspray
Motstandsdyktig mot kjemikalier og værpåvirkninger
Utmerket vedheft

Fysiske og kjemiske data

Base: EP-2 fett
Kolourname: white
Lukt: Karakteristisk
Overflater: Brake systems
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt: n.a.
Lagringsstabilitet: 10 y
Innhold: 500 ML

Hvordan bruke

Les instruksjonene nøye før bruk.
Beste behandlingstemperatur er mellom 10 og 25 °C.
Rist boksen godt før bruk.
Spray bremsedelene som skal behandles før montering.
Bremsefett kan fjernes med MOTIP Brake Cleaner.
Unngå kontakt med bremseskive og bremseklosser!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com