MOTIP Gasket Remover

Technical Information



Fjern tørkede lim og tetninger, samt herdet tetningsmateriale raskt og enkelt fra bil- og maskindeler med MOTIP Gasket Remover. Egnet for sylinderhoder, girkasser, eksos, carters, rørleggerarbeid, vann- og oljepumper og elektriske motorer. MOTIP Gasket Remover har utmerkede oppløsende egenskaper, er ikke-ledende, ikke-etsende, er svært tyktflytende og brukervennlig med en presis spray.

Bestillingsnummer: 090403

Kvalitet og egenskaper

Optimal effekt med tanke på høy viskositet
Lett gelstruktur
Høye oppløsningsegenskaper
Ikke-ledende og ikke-etsende
Rettet jetspray
360° ventil
Brukervennlig

Fysiske og kjemiske data

Base: Metylal
Kolourname: no colour
Lukt: Karakteristisk
Overflater: Cylinder Heads, Gear Boxes, Exhausts, Crankcases, Sanitary Fittings, Water and oil pumps, Electro engines
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt: n.a.
Lagringsstabilitet: 10 y
Innhold: 500 ML

Hvordan bruke

Les instruksjonene nøye før bruk.
Boksen skal ha romtemperatur.
Beste behandlingstemperatur er mellom 10 og 25 °C.
Rist boksen godt før bruk.
Dekk til lakkerte deler og plastdeler.
Påfør i et likt lag på delene som skal behandles og la det virke i ca. 10 minutter.
Fjern de oppløste restene forsiktig med en påfyllingskniv. Gjenta behandlingen med vedvarende kontaminasjon.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 6, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com