MOTIP Paint Remover

Technical Information



Fjern gamle lag med maling fra overflater av stein, betong, asfalt, metall og tre med MOTIP Paint Remover. Paint Remover har en gelstruktur og er brukervennlig.

Bestillingsnummer: 090410

Kvalitet og egenskaper

Spraymønster ca. 8 centimeter bredt
Gelstruktur
Svært effektiv
Brukervennlig
Also suitable for various specialty paints, such as camouflage paints and hammerfinish paints.

Fysiske og kjemiske data

Base: Metylal
Kolourname: no colour
Lukt: Karakteristisk
Overflater: Paintwork, Stonework, Pavement
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt: n.a.
Lagringsstabilitet: 10 y
Innhold: 500 ML

Hvordan bruke

Les instruksjonene nøye før bruk.
Boksen skal ha romtemperatur.
Beste behandlingstemperatur er mellom 10 og 25 °C.
Rist boksen før bruk og test overflatens kompatibilitet.
Påfør malingsfjerner sjenerøst og la det virke. Tiden som trer i kraft avhenger av kvaliteten og alderen på lakken som skal fjernes.
Fjern deretter med et verktøy som passer for dette formålet. Gjenta behandlingen ved behov.
Forurenset malingsfjerner skal betraktes som kjemisk avfall.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 6, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com