MOTIP Rask start

Technical Information



Bruk MOTIP Quick Start for å eliminere startproblemer med forbrenningsmotoren for både bensin- og dieselmotorer. Sprayen er eterbasert.

Bestillingsnummer: 090405, 290405

Kvalitet og egenskaper

Hurtigvirkende
Eter-basert
Tåkespraymønster

Fysiske og kjemiske data

Base: Dietyleter med mineralolje
Kolourname: no colour
Lukt: Karakteristisk
Overflater: Diesel engines, Petrol engines
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt: n.a.
Lagringsstabilitet: 10 y
Innhold:
- 500 ML
- 200 ML

Hvordan bruke

Les instruksjonene nøye før bruk.
Boksen skal ha romtemperatur.
Rist boksen godt før bruk.
Injiser hurtigstart i luftinntaket til luftfilteret i flere sekunder.
Start motoren.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com