MOTIP RAL Acryl Spray

Technical Information



Hurtigtørkende spraymaling med høy dekning og fylleegenskaper for profesjonell bruk. Til behandling av overflater, behandlet og ubehandlet, av tre, metall, aluminium, glass, stein og ulike typer plast. Lakken har en varig glans og farge, er ripefri og støtsikker og er rustforebyggende. MOTIP RAL Acryl Spray er ikke-falmende og UV-bestandig og motstandsdyktig mot værpåvirkninger.

Bestillingsnummer: 07000, 07001, 07002, 07003, 07004, 07005, 07006, 07007, 07008, 07009, 07010, 07011, 07012, 07013, 07014, 07015, 07016, 07017, 07018, 07019, 07020, 07022, 07023, 07024, 07025, 07026, 07027, 07028, 07029, 07030, 07031, 07032, 07033, 07034, 07035, 07036, 07037, 07039, 07040, 07042, 07045, 07046, 07054, 07055, 07056, 07057, 07060, 07061, 07062, 07063, 07064, 07065, 07067, 07068, 07069, 07071, 07072, 07073, 07074, 07075, 07076, 07077, 07078, 07079, 07080, 07081, 07082, 07085, 07086, 07087, 07088, 07089, 07090, 07091, 07092, 07096, 07121, 07122, 07123, 07124, 07125, 07126, 07127, 07128, 07129, 07130, 07131, 07132, 07133, 07134, 07135, 07136, 07137, 07138, 07139, 07140, 07141, 07142, 07143, 07144, 07145, 07146, 07147, 07148, 07149, 07150, 07151, 07152, 07120, 07119, 07118, 07117, 07116, 07115, 07114, 07113, 07112, 07111, 07110, 07109, 07108, 07106, 07104, 07103, 07102, 07100, 07153, 07154, 07155, 07156, 07157, 07158, 07159, 07164, 07166, 07167, 07168, 07169, 07170, 07171, 07216, 07224, 07236, 07238, 07165, 907037, 907040, 907042, 907045, 907090, 907238, 907012, 907019, 907020, 907034, 907062, 907088, 907110, 907128, 907224, 907236

Kvalitet og egenskaper

Hurtigtørkende
Utmerket dekning og fylleegenskaper
Varig farge og varig glans
Ripefri og støtsikker
Motstandsdyktig mot værpåvirkninger
Korrosjonsforebyggende
UV-bestandig og falmer ikke
God vedheft

Fysiske og kjemiske data

Base: Akryl harpiks
Kolourname:

- green blue
- sapphire blue
- cobalt blue
- sulfur yellow
- gentian blue
- steel blue
- ultramarine blue
- pure orange
- violet blue
- traffic blue
- patina green
- black green
- sky blue
- turquoise green
- light blue
- signal grey
- brilliant blue
- capri blue
- basalt grey
- iron grey
- anthracite grey
- blue grey
- platinum grey
- dusty grey
- umbra grey
- silver grey
- traffic grey b
- traffic grey a
- silk grey
- stone grey
- red brown
- flint grey
- sepia brown
- light grey
- grey brown

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com

- papyrus white
- traffic white
- quartz grey
- pure white
- signal white
- cream white
- grey white
- brown beige
- lemon yellow
- oyster white
- ivory
- broom yellow
- dahlia yellow
- light ivory
- zinc yellow
- saffron yellow
- grey beige
- sand yellow
- beige
- signal yellow
- traffic yellow
- gold yellow
- honey yellow
- colza yellow
- maize yellow
- daffodil yellow
- melon yellow
- yellow orange
- pastel orange
- deep orange
- red orange
- traffic orange
- bright red orange
- vermilion
- beige red
- traffic red
- antique pink
- flame red
- light pink
- raspberry red
- carmine red
- leaf green
- claret violet
- fir green
- reseda green
- purple violet
- grass green
- yellow green
- moss green
- white green
- light green
- pale green
- telemagenta
- black blue
- signal blue
- azure blue
- pigeon blue
- water blue
- night blue
- pastel blue
- olive green
- blue green
- yellow olive
- may green
- opal green
- mint green
- squirrel grey
- beige grey
- slate grey
- black grey
- concrete grey
- graphite grey

- agate grey
- traffic green
- emerald green
- turquoise blue
- red violet
- blue lilac
- red lilac
- heather violet
- nut brown
- traffic purple
- fawn brown
- chocolate brown
- copper brown
- wine red
- purple red
- oxide red
- black red
- signal red
- ruby red
- window grey
- ochre brown
- clay brown
- mahogany brown
- terra brown
- graphite black
- traffic black
- deep black
- mouse grey
- grey blue
- signal green
- signal brown
- brown red
- grey aluminium
- white aluminium

Lukt: Karakteristisk

Grad av glans:

- høyglans, >85
- matt, 10 ±2
- halvmatt, 25 ±5
- glans, >75

Effektivitet:

- 400 ML – 1.25 - 1.75 m²
- 12 ML – small spots m²

Støvtørr: 5 - 10 min

Tørr å ta på: 10 - 20 min

Helt tørr: 120 min

Overstrøkbar: 120 min

Overflater: wood, metal, aluminium, glass, stone and various types of plastic

Minimum arbeidstemperatur: 10 °C

Maksimal arbeidstemperatur: 25 °C

Flammepunkt:

- n.a.
- 27

Temperaturbestandighet: 80 °C

Lagringsstabilitet:

- 10 m
- 5 m

Innhold:

- 400 ML
- 12 ML

Hvordan bruke

Les instruksjonene nøye før bruk.
Overflaten skal være ren, tørr og fri for fett. Fjern løs gammel lakk og rust og slip overflaten med sandpapir.
Påfør et lag med MOTIP Primer som passer til overflaten. Etter tørking, slip underlaget (grovhet 600).
Overflaten skal være ren, tørr og fri for fett. Boksen skal ha romtemperatur. Beste behandlingstemperatur er mellom 10 og 25 °C.
Rist boksen i 2 minutter og spray en prøve før bruk. Avstand til overflaten som skal behandles skal være ca. 25 til 30 centimeter.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com

Påfør lakken i flere tynne lag. Før du påfører neste lag, må du riste boksen igjen.
Rengjør spraydysen etter bruk (snu boksen opp ned og trykk på spraydysen i ca. 5 sekunder).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com