MOTIP Voksbelegg 1 l

Technical Information



Unngå rust på bilen med MOTIP Anti-Rust Waxcoating. Voksbelegg er motstandsdyktig mot vær, salt, vann og svake syrer og baser, har en utmerket rustforebygging og kan påføres i tykke lag.

Bestillingsnummer: 00130, 00136

Kvalitet og egenskaper

Skal påføres med en UBC spraypistol
Utmerket korrosjonsforebygging
Utmerket vedheft
Motstandsdyktig mot værpåvirkninger
Motstandsdyktig mot salt, vann og svake syrer og baser
Kan påføres i tykke lag

Fysiske og kjemiske data

Base: Voks
Kolourname:
- transparent brown
- black

Lukt: Karakteristisk
Effektivitet: 1,00 L – 2 - 3 m²
Overflater: Untreated metal
Minimum arbeidstemperatur: 10 °C
Maksimal arbeidstemperatur: 25 °C
Flammepunkt:
- 37
- 37 °C

Lagringsstabilitet:
- 5 y
- 1.5 y

Innhold: 1,00 L

Hvordan bruke

Les instruksjonene nøye før bruk.
Boksen skal ha romtemperatur. Beste behandlingstemperatur 10 til 25 °C. Rist boksen før bruk. Arbeidstrykk 4 til 5 bar.
Påfør voksbelegget i ønsket lagtykkelse.
Rengjør spraypistolen med white spirit etter bruk.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com