MOTIP Copper Spray (Drum)

Technical Information



Unngå slitasje og klebing av skruforbindelser utsatt for svært høye temperaturer med MOTIP Copper Grease. Kobberfett har høy termisk stabilitet og er korrosjonsforebyggende. MOTIP Copper Grease er motstandsdyktig mot temperaturer på -40 °C opp til + 1.100 °C.

Bestillingsnummer: V05561

Kvalitet og egenskaper

Forenkler fremtidig fjerning
Høy termisk stabilitet
Motstandsdyktig mot kjemikalier og værpåvirkninger
Forhindrer slitasje og feste
Korrosjonsforebyggende
Utmerket vedheft
Rettet jetspray

Fysiske og kjemiske data

Base: EP-2 Fett med kobber
Kolourname: copper
Overflater: Brake parts, Exhaust parts, Screwed connections (which are exposed to high temperature), Battery Poles, Thread of Spark Plugs
Flammepunkt: -40 °C
Innhold: 5,00 L

Hvordan bruke

Les instruksjonene nøye før bruk.
Boksen skal ha romtemperatur.
Beste behandlingstemperatur er mellom 10 og 25 °C.
Rist boksen godt før bruk.
Påfør kobberspray. Den spesifikke smøreegenskapen oppnås etter fordampning av løsningsmidlet (ca. 1 minutt).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 5, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com